



Products >

Home > Fan Series

- [New Products](#)
- [Fan Series](#)
- [Thermal Module](#)
- [Application](#)
- [OSmart AC Fan](#)
- [Accessories](#)

Fan Series



Please choose type

- AC FAN
- Blower
- DC Chip cooler
- DC FAN
- Waterproof Fan
- Model Numbering Scheme

Select a Fan / Blower

Fan = DC-Fan      Size = 80x80x15      Speed =      Flow =      Noise =



Bearing type: ●=Ball ※=Sleeve ●=Hypro Bearing

Frame Size	Model No	Bearing	Volt. (VAC)	Current (A)	Speed (rpm)	Air Flow (CFM)	Pressure (InAq)	Noise (dB/A)	PDF
80x80x15	AD0805MB-D73(N)	●※●	5	0.13	2440	21.805	0.078	24.9	
80x80x15	AD0805HB-D73(N)	●※●	5	0.22	3200	29.722	0.122	34.4	
80x80x15	AD0812LB-D73(N75)	●※●	12	0.04	2000	18.335	0.052	18.8	
80x80x15	AD0812MB-D73(N75)	●※●	12	0.05	2440	21.805	0.078	24.9	
80x80x15	AD0812HB-D73(N75)	●※●	12	0.11	3200	29.722	0.122	34.4	
80x80x15	AD0812UB-D73(N75)	●※●	12	0.16	3800	34.338	0.173	38.1	
80x80x15	AD0824MB-D73(NEUM)	●※●	24	0.05	2440	21.805	0.078	24.9	
80x80x15	AD0824HB-D73(NEUM)	●※●	24	0.08	3200	29.722	0.122	34.4	
80x80x15	AD0824UB-D73(NEUM)	●※●	24	0.08	3800	34.338	0.122	38.1	
80x80x15	AD0824UB-D73(NEUM)	●※●	24	0.08	3800	34.338	0.122	38.1	
80x80x15	AD0824XB-D73(NEUM)	●※●	24	0.10	4300	39.300	0.205	42.3	
80x80x15(7)	AD0812LB-D7B(NS75)	●※●	12	0.05	2500	22.950	0.084	25.8	
80x80x15(7)	AD0812MB-D7B(NS75)	●※●	12	0.07	3000	28.629	0.128	30.9	
80x80x15(7)	AD0812HB-D7B(NS75)	●※●	12	0.09	3500	31.500	0.150	36.5	
80x80x15(7)	AD0812UB-D7B(NS75)	●※●	12	0.14	4000	36.751	0.197	39.6	
80x80x15(7)	AD0812XB-D7B(NS75)	●※●	12	0.18	4500	41.775	0.246	43.4	
80x80x15(7)	AD0812VB-D7B(NS75)	●	12	0.23	5000	46.000	0.290	46.5	

80x80x15(gp)	AD0812LB-D93GP	⊗※●	12	0.07	2000	22.635	0.057	22.1	
80x80x15(gp)	AD0812MB-D93GP	⊗※●	12	0.11	2500	28.906	0.085	29.6	
80x80x15(gp)	AD0812HB-D93GP	⊗※●	12	0.13	3000	35.522	0.131	35.3	
80x80x15(gp)	AD0812UB-D93GP	⊗※●	12	0.18	3500	40.690	0.163	39.7	
80x80x15(gp)	AD0812XB-D93GP	⊗※●	12	0.29	4000	46.353	0.197	42.7	
80x80x15(t-7)	AD0812LB-D76(T)	⊗※●	12	0.06	2000	18.335	0.052	18.8	
80x80x15(t-7)	AD0812MB-D76(T)	⊗※●	12	0.08	2440	21.805	0.078	24.9	
80x80x15(t-7)	AD0812HB-D76(T)	⊗※●	12	0.11	3200	29.722	0.122	34.4	
80x80x15(t-9)	AD0812DB-D96(T)	⊗※●	12	0.07	2500	24.958	0.086	30.2	
80x80x15(t-9)	AD0812LB-D96(T)	⊗※●	12	0.10	3000	29.581	0.117	36.0	
80x80x15(t-9)	AD0812MB-D96(T)	⊗※●	12	0.14	3500	34.897	0.155	40.4	
80x80x15(t-9)	AD0812HB-D96(T)	⊗※●	12	0.20	4000	40.111	0.195	44.5	
80x80x15(t-9)	AD0812UB-D96(T)	⊗※●	12	0.26	4500	45.019	0.248	48.0	
80x80x15(t-9)	AD0824DB-D96(T)	⊗※●	24	0.04	2500	24.958	0.086	30.2	
80x80x15(t-9)	AD0824LB-D96(T)	⊗※●	24	0.05	3000	29.581	0.117	36.0	
80x80x15(t-9)	AD0824MB-D96(T)	⊗※●	24	0.06	3500	34.897	0.155	40.4	
80x80x15(t-9)	AD0824HB-D96(T)	⊗※●	24	0.10	4000	40.111	0.195	44.5	
80x80x15(t-9)	AD0824UB-D96(T)	⊗※●	24	0.14	4500	45.019	0.248	48.0	

**Note:**

1. The figure shown in "current" column is the actual current which is different from the current of safety regulation.If you need the data sheet or more info, please contact with our sales. Thanks!

2. " \* " stands for "Preliminary" model

