



ELASTIC LOOP TAPES

The Velcro companies offer two elasticized loop tapes for applications in which closure expansion and contraction is required.

VELSTRETCH® Brand Loop 151

This stretch loop is designed to provide about 55% elongation and is a relatively high-power tape. The nylon and synthetic rubber materials used in the construction of this woven product provide moderate to high cycles in use with recommended Hook #65. The plush backing makes this tape ideal for applications where comfort, as well as a secure fit, is desired. Examples: soccer shin guards, scuba diving equipment straps and assemblies holding respiratory devices in place.

VELCRO® Brand Loop 152

VELCRO® brand Loop 152 provides breathability, 90% stretch and is relatively low-power. The nylon and synthetic rubber combination in this knitted product performs best with Hook #88 and Hook HTH 705. Because of its more open construction and lower cost, VELCRO® brand Loop 152 is designed for short and moderate use in applications like fetal monitoring belts.

Product	Suggested Usage	Suggested Hooks	Shear Strength	Peel Strength	Standard Width
VELSTRETCH® brand Loop 151	Daily-used devices requiring fair support	#65	4.5 PSI	.70 PIW	5/8", 3/4", 1", 1 1/2", 2"
VELCRO® brand Loop 152	Low to moderate cycle applications	#88 HTH 705	6.7 PSI 8.5 PSI	1.98 PIW 2.30 PIW	1", 1 1/2", 2"

VELCRO® brand Loop 152 is available in WHITE only. VELSTRETCH® brand loop is stocked in WHITE, BLACK and BEIGE. Custom colors are available – please inquire.
Standard Packaging – 40 Yard Rolls/25 Yard Rolls

IMPORTANT NOTE TO PURCHASER

All statements, technical advice and recommendations contained herein are based on tests believed to be reliable, but the accuracy thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace the quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

FOR SALES AND TECHNICAL INFORMATION,
PLEASE CONTACT OUR MANCHESTER, NH SALES HEADQUARTERS AT (800) 225-0180.

SALES OFFICES AND DISTRIBUTION CENTERS WORLDWIDE

Velcro USA Inc.
406 Brown Avenue
Manchester, NH 03103
Telephone: (603) 669-4892
Facsimile: (603) 669-9271
E-Mail: marketing@velcro.com

Velcro Canada Inc.
114 East Drive
Brampton, ONT, L6T 1C1, Canada
Telephone: (905) 791-1630
Facsimile: (905) 791-5329
E-Mail: canada@velcro.com

<http://www.velcro.com>

Velcro USA Inc. and Velcro Canada Inc. are ISO-9001 and QS9000 registered companies

For transportation sales, please contact Velcro USA Inc., Automotive Division, 1210 Souter, Troy, MI 48083 • (248) 583-6060

