



REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	CABLE LENGTH
P1	1	+3.3V	ORANGE	18	MOLEX 39-01-2200 or EQUIV.	200 +15 -0 mm
	2	+3.3V	ORANGE	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
	5	COM	BLACK	18		
	6	+5V	RED	18		
	7	COM	BLACK	18		
	8	PW-OK	GRAY	24		
	9	+5Vsb	PURPLE	20		
	10	+12V	YELLOW	18		
	11	+3.3V	ORANGE	18		
		+3.3VSENSE	BROWN	24		
	12	-12V	BLUE	24		
	13	COM	BLACK	18		
	14	PS-ON	GREEN	24		
	15	COM	BLACK	18		
	16	COM	BLACK	18		
	17	COM	BLACK	18		
	18	-5V	WHITE	24		
	19	+5V	RED	18		
20	+5V	RED	18			
P3	1	+12V	YELLOW	18	MOLEX 15-24-2000 or EQUIV.	250 +15 -0 mm
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
PA	1	+12V	YELLOW	22	AMP 171822-4 or EQUIV.	300 +15 -0 mm
	2	COM	BLACK	22		
	3	COM	BLACK	22		
	4	+5V	RED	22		
P4	1	+12V	YELLOW	18	AMP 1-480424-0 or EQUIV.	200 +15 -0 mm
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
PB	1	COM	BLACK	20	MOLEX 39-01-2040 or EQUIV.	350 +15 -0 mm
	2	COM	BLACK	20		
	3	+12V	YELLOW	20		
	4	+12V	YELLOW	20		

NOTE:

1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.

SPI P/N:FSP180-60SAV-B P/N.:9PA1800906

MODEL NO. : FSP180-60SAV(S031)		TITLE: ASSY		SHEET: 1 OF 1		REV:01
R&D	PE	DRAWN	DATE			
陳炳旭 4/4	黃銀山 4/4/2002	陳雅慧	MAY.11.2002			
INTERIOR COUNTERSIGN:		賴俊宏 4/4 '02				

