



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: SRWF5U

SmartRack 5U Low-Profile Wall Mount Rack Enclosure Cabinet



Highlights

- Designed for IT and education environments where equipment needs to be secure and out of the way
- 5U with adjustable/reversible rackmount rails
- 2U slide-out mounting brackets for patch panels
- Locking, reversible front door
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Description

The SRWF5U 5U+2 Low-Profile Wall Mount Rack Enclosure Cabinet is designed to integrate wall-mounting, easy equipment access, and cable management in IT network applications with limited floor space. Ventilated front door and bottom panels allow generous airflow to keep equipment operating safely. Adjustable horizontal rack rails securely mount 5U of 19" rackmount equipment with M6 or they can be reversed for securing with 12-24 threaded mounting holes. The patch panel mounting brackets provide space for up to 2U of patch panels with integral slide-out feature for easy cable access. Supports up to 150 lbs of equipment.

Applications

IT network environments, back office, and network closets with limited floor space and classrooms where equipment needs to be secure and out of the way of students.

Package Includes

- SRWF5U Low-profile wall-mount enclosure
- (12) M6 screws
- (12) M6 cup washers
- (12) 12-24 screws
- (2) Keys
- Owner's Manual

Features

- 5U low-profile wall-mounted enclosure
- Adjustable horizontal mounting depths from 17" to 20" inches
- Slide-out mounting brackets provides 2U of space for patch panel(s)
- Ventilated front door and bottom panels for increased airflow
- Locking, reversible front door
- Multiple keyhole mounting slots for wall mounting
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) compliance

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	20

Installed whole system maximum rack depth (cm)	50.80
Installed whole system minimum rack depth (inches)	17
Installed whole system total rack space height (rack spaces)	5U
Shipping weight (lbs)	49
Shipping weight (kg)	22.1
Shipping Dimensions (HWD/in)	31.5" x 27.6" x 12"
Shipping Dimensions (HWD/cm)	80.01 x 70.10 x 30.48
Unit weight (lbs)	29
Unit weight (kg)	13
Unit Dimensions (cm)	73.15 x 65.02 x 24.64
Unit Dimensions (in)	EXTERNAL DIMENSIONS: 28.8" x 25.6" x 9.7" (HWD)
Color	Black
Weight Capacity - Stationary (lbs)	150
Installed whole system minimum rack depth (cm)	43.18
Weight Capacity - Stationary (kg)	68.0
CERTIFICATIONS	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	UL60950; RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Environmental Monitoring	SRSWITCH	Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE	1
Patch Panels	N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
Patch Panels	N252-024	24-Port Cat6 Patch Panel 568B, 1U	1
Patch Panels	N252-048	48-Port Cat6 Patch Panel 568B	1
Rack Accessories	SRFANWM	Wall-Mount Roof Fan Kit, 120V (2 high-performance fans; 5-15P plug)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5047.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.