



## **SPECIFICATION GUIDELINE FOR SR Series Swing Racks**

GL24SR – 23.75”H x 20.75”W x 18.00”D – 12 RMU

GL36SR – 36.00”H x 20.75”W x 18.00”D – 19 RMU

GL48SR – 48.75”H x 20.75”W x 18.00”D – 26 RMU

### **General**

The Wall Mount Swing Racks (SR) must be UL listed to UL60950-1 (Standard for Information Technology and Communications Equipment, Cabinet, Enclosure and Rack Systems.) The Wall Mount Swing Rack shall be constructed out #14 & 16 Gauge cold rolled steel (CRS) (GL48SR is made out of 12 GA). Manufacturer must be ISO 9001:2008 registered.

### **Common features:**

- The Swing Racks will ship unassembled.
- The Swing Racks shall have 16.00” of usable depth
- Rack mounting shall be tapped #12-24 on the front and rear flange.
- A package of #12-24 hardware shall be included.
- Weight capacity shall be 100 lbs.
- Multiple mounting provision for cable management cinch strap or wire ties.
- The rack mount section will be able to swing a full 180 degrees with a positive stop.
- Easy release hinge pins allow quick access to the back of mounted equipment.
- Wall mounting shall be done on 16” on center using keyway holes.
- Swing Racks shall be painted using durable black powder coat paint.