

RECOMMENDED



Gladius Smart To THE-7435



## Gladius Smart To THE-7435

Ref: To THE-7435

TPV Of big robustness, thought for critical surroundings of work. Team 100% fanless without ningun mechanical component. Carcasa Of alloy of steel with aluminium.

The Signpost LED of 100.000 Hours and Industrial component in plate and source of feeding ensure a time of life of the very long system

It incorporates of series a plate IO additional with 24V for the printers of ticket together with two ports RS232 standar

- Signpost industrial screen Mitsubishi 100.000 hours LED 450cd.
- Tactile ELO resistivo 5 threads
- Industrial plate IEI
- External industrial source
- Finder LCD 2x20 included (excepto model hang in wall)
- Team Fanless
- Serial ports 5v/12v
- 24v DC Out for printers Epson



### Specifications

### Accessories

### Downloads

**Models:** To THE-7435 15" Base standar  
To THE-7435 15" Base with support for Printer  
To THE-7435 15" Basic low profile  
To THE-7435 15" WITHOUT base to Hang in wall (Std. VESA)

**Carcasa:** Steel with aluminium

**Screen:** Screen Mitsubishi 15" 1024x768 450 cd/m<sup>2</sup> (LED 100.000 Hours)

**Tactil:** ELO Resistiva 5 Threads

**Operational:** Processor Intel® Atom, D525, 1M L2 Cache, 1.8Ghz  
Memory of system 1 GB Standard, Maximum 4 GB (1 x 204 pins DDR3)  
Chipset Graphic Intel® GMA 3150  
Source Feeding 150W (12V/7.5To) external Feeding  
Feeding 24V for Printers  
Disk of storage 1 x 2.5", SATA HDD or SATA SSD

**IO:** Serial ports 3 x Internal: COM3 (Touch), COM5 (LCM), COM6 (Reserved)  
3 x External : COM1, COM2 (DB9), COM4 (RJ45)  
USB Port 4 x Internal (1 MSR, 3 Reserved), 5 x External (4 Rear, 1 Front)  
Parallel port 1 x Bi-directional Parallel Port  
Drawer Port 1 x RJ11 (12V)  
Keyboard / Mouse 1 x PS/2  
LAN Port 1 x RJ45 Giga LAN  
PCI Slot 1 x Mini PCI-and (Internal)  
Video Port 1 x VGA  
Audio Port 1 x Line-out, 1 x Mic-in  
DC Output 1 x 12V DC Jack 2.5 mm  
2ª PLATE IO  
Type To (Standar) Serial Port: COM5 & COM3 (RJ45) with RI / 5V / 12V Selectable, DC Output: 1 x 24V, 1 x Mic In  
Type B (Special Requirements) Serial Port: COM5 & COM3 (RJ45) RI / 5V / 12V Selectable, Powered USB Port: 1 x 24V, 1 x Mic In  
Type C Serial Port: COM5 & COM3 (RJ45) RI / 5V / 12V Selectable, Powered USB Port: 1 x 12V, 1 x Mic In

To THE-7435 15" Base with support for Printer -> 382 x 294 x 480 mm  
To THE-7435 15" Basic low profile -> 382 x 310 x 310 mm  
To THE-7435 15" WITHOUT base to Hang in wall (Std. VESA) -> 382 x 310 x 65 mm

**Surroundings:** Surroundings:  
EMI / Safety CE, FCC Class To  
Operative temperature 0 °,C ~ 40 °,C (32 °,F ~ 104 °,F)  
Temperature of Storage -10 °,C ~ 55 °,C (14 °,F ~ 131 °,F)  
Relative humidity 10% ~ 90% (no condensed)

**Operating system:** Operating systems:  
Windows XP, POSReady 2009, Windows 7, POSReady 7  
Linux Ubuntu 8,04 LTS

**Guarantee:** 2 Years

[Terms and condition](#) | [Map web](#) | [Contact](#)

Copyright © 2012 Fitich Enterprises CO, LTD. All rights reserved | PARC BUSINESS GRANLAND - Of the Muslim, 18 | 08918 - Badalona |  
Tel: 934 | 406 103 Fax: 934 | 499 790 ventas@fecpos.es  
Comitium | BAB